

Texecom Connect SmartCom




Connect your panel to any local area network

The Texecom Connect SmartCom is an ethernet communicator that facilitates the Texecom Connect experience by connecting any Premier Elite control panel to a local area network.

Texecom Connect integrates with Texecom's flagship security systems, the Premier Elite Series, to allow you to take direct control of your home and your security. Control the operation of your security system, receive notifications of system events and monitor cameras or activity from anywhere in the world.

Communicating exclusively using outbound connections, The Texecom Connect SmartCom removes the need to open any router ports, ensuring simplicity of installation and maximum security.

As such, any installation that has a reliable internet connection can benefit from Texecom Connect with the addition of the Texecom Connect SmartCom.



Connect **your** life to your
home and your **security**



Connect your life to your home and your security

The Timeline

Central to the Texecom Connect App experience is the timeline. Both past and programmed events are clearly presented, giving the user instant access to review events that have transpired.



Calendar

- See all the events of the day
- Arranged by system status
- Go back and review previous days
- View stored video linked from the calendar or watch a live video stream



Rooms & Devices

Devices are allocated to rooms within the Texecom Connect App, which makes locating devices and creating home automation recipes from multiple devices in a room easy and intuitive.

Recipes



Recipes are a user-friendly way of describing the programming actions that are used for automation. The Texecom Connect App is programmed on the basis of cause and effect.



Texecom Connect SmartPlug

Control any mains-powered device remotely with the Texecom Connect SmartPlug. This *Ricochet*® enabled wireless plug sits between a wall socket and the power plug of a device, and is controlled via the Texecom Connect App.



Standards & Specifications

Alarm System	EN50131-1, PD6662, Grade 2 Class II
Product Type	CELA0000
Ethernet	10/100 Base-T, 100 Base-TX
WiFi Module	2.4Ghz IEEE802.11 (b/g/n)
Max RF Power	15 dbm - internal antenna
Operating Voltage	8 - 15V DC
Typical Current	150mA
Relative Humidity	0 - 95% non-condensing

Dimensions & Weight

