



Surface Magnetic Contact


Code: SC570/GY/G3/EN

SC570 | Surface Contact | Grade 3 | Anthracite Grey | Non-resistored

This magnetic door contact can be used in most security systems up to and including grade 3 and environmental class II as specified in EN50131-1 and is certified to EN50131-2-6 by Kiwa FSS. This contact can be used on windows and doors to detect the unauthorised entry of an intruder. The contact is also protected against tampering with optional detection of removal from its mounting surface.

Features & Benefits

- 6 Terminals
- Cover and wall tamper
- Available in white, brown or anthracite grey
- Magnetic Detection
- EN50131-2-6 Grade 3
- Environmental Class II



Product Information

Security Grade

3

CQR Security, 125 Pasture Road, Moreton, Wirral, CH46 4TH

Sales: +44(0)151 6061000 (9am to 5pm Monday to Friday) **Tech:** +44(0)151 606 6311

sales@cqr.co.uk | www.cqr.co.uk

Company Registration Number: 5192024 | VAT Number: 309 0409 27



Environmental Class	Class II
Standards	EN50131-1, EN50131-2-6, EN50130-5
Tamper Protection	Cover / RFMS & MID
Warranty	2
Connection type	Wired

Housing

Colour	Anthracite Grey
Material	HIPS

Electrical

Connection type	Wired
No. of terminals	6 Terminal
Contact type	Normally Closed
Contact Material	Rhodium & Ruthenium

Features

Mode of operation	DP
Operation Axes (X, Y, Z)	X, Y
Pull-in gap (X, Y, Z)mm	12, 10
Suitable for Double Door	Yes
No. of terminals	6 Terminal

