

**6701W****MINI MONITOR, S2**

Wall-mounted colour monitor with 4.3" 16/9 screen and handset. Allows brightness and contrast control, plus adjustment of the volume of the ringtone, which can be customised with a choice of different melodies. Equipped as standard with 4 soft touch buttons for door-opening, self-ignition, switchboard call and privacy service functions and with door status indicator LEDs. Manages floor door calls as standard. Option of adding 4 additional buttons with accessory Art. 6733W. Complete with 2 x 8-position DIP-switches for user code programming and button programming. Includes wall-mounting or residential series box backplate and riser distribution terminal Art. 1214/2C. The monitor can only be used in 2-wire Simplebus2 systems. Dimensions: 175x160x22mm.

AWARDSDESIGN
MILANO


6701W

MINI MONITOR, S2

GENERAL DATA

Product height (mm)	160
Product width (mm)	175
Product depth (mm)	22
Product weight (g)	600
Product color	White RAL9003
Material	ABS
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes

DISPLAY FEATURES

Size (inches) (")	4.3
Aspect Ratio	16:9
Resolution (pixels)	480x272

AUDIO FEATURES

Microphone	6mm (Ø), Omnidirectional
Loudspeaker	40 (ø) x 5.1 (H)mm, 100 ohm, 0.25W

ELECTRICAL CHARACTERISTICS

Type of power supply	Power supply from video door entry bus
Supply voltage	22÷34 VDC (Bus)
Maximum absorption (W)	5.4


6701W

MINI MONITOR, S2

HARDWARE FEATURES

Type of buttons	Capacitive
Service buttons	Lock-release, Silent (Privacy), Door open
No. of programmable buttons for additional functions	2 (6 with accessory art. 6733W)
Clamps	L L CFP1 CFP2
Removable terminals	Yes

SETTINGS

Ringtone volume	Yes
Screen brightness	Yes
Screen colour	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection degree	IP30
Operating temperature (°C)	5 ÷ 40
Operating humidity (RH max - %) (%)	25 ÷ 75
Environmental class	I
Compliance and Certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS

Door opener	Yes
Self Activation	Yes
Intercom calls	Yes
Actuator control	Yes
CPS call	Yes
Outside door call input	Yes
Silent mode (Privacy)	Yes
Door opening on call (Doctor)	Yes
Door open signaling	Si



6701W

MINI MONITOR, S2

MAIN FUNCTIONS

Multiple address	Yes
Customisable ringtone	Yes
Sending alarm calls	Yes

**6701W****MINI MONITOR, S2****ACCESSORIES****6712A DESK BASE FOR MINI S2 MONITOR WITH HANDSET**

Desk base installation accessory for Mini monitor with handset in Simplebus 2 system.

**6711WS MINI HANDSET SMALL ADAPTER PLAQUE**

Mounting accessory for Mini Monitor when replacing Magis or Genius door entry monitors. White. Dimensions: 230x220x3mm.

**6719W Access. cables external passage for MINI HS. S2**

Wall support bracket for Mini monitor with handset allowing thru-routing of external cables.

**6711W ADAPTER PLAQUE FOR MINI MONITOR W/ HANDSET. WHITE.**

Mounting accessory for Mini Monitor when replacing Magis or Genius door entry monitors. Complete with backplate art. 6710 and distribution terminal art. 1214/2C. White. Dimensions: 300x270x3 mm.

**6733W ADDITIONAL BUTTONS KIT FOR MINI MONITOR, WHITE**

Accessory for transforming MINI monitors Art 6700W-/BM and 6701W-/BM into versions with 8 buttons. Includes an 8-button faceplate and an electronic module for activating the buttons, which can be installed quickly without opening up the monitor.